

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: Pozzolan

1.2. Intended Use of the Product

Use of the Substance/Mixture: No use is specified

1.3. Name, Address, and Telephone of the Responsible Party

Company

CalPortland Company
 10655 W Park Run Drive, Suite 275
 Las Vegas, NV 89144
 T 626-852-6200

www.calportland.com

1.4. Emergency Telephone Number

Emergency Number : 626-852-6200

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US Classification

Skin corrosion/irritation Category 1B	H314
Serious eye damage/eye irritation Category 1	H318
Carcinogenicity Category 1A	H350
Specific target organ toxicity (single exposure) Category 3, Respiratory tract irritation	H335
Specific target organ toxicity (repeated exposure) Category 1	H372

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US) :



Signal Word (GHS-US) :

Danger

Hazard Statements (GHS-US) :

H314 - Causes severe skin burns and eye damage.
 H318 - Causes serious eye damage.
 H335 - May cause respiratory irritation.
 H350 - May cause cancer (Inhalation).
 H372 - Causes damage to organs (lung/respiratory system) through prolonged or repeated exposure (Inhalation).

Precautionary Statements (GHS-US) :

P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P260 - Do not breathe dust.
 P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
 P270 - Do not eat, drink or smoke when using this product.
 P271 - Use only outdoors or in a well-ventilated area.
 P280 - Wear protective gloves, protective clothing, and eye protection.
 P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.
 P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.
 P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313 - If exposed or concerned: Get medical advice/attention.
 P310 - Immediately call a poison center or doctor.
 P314 - Get medical advice/attention if you feel unwell.
 P321 - Specific treatment (see section 4 on this SDS).
 P363 - Wash contaminated clothing before reuse.

Pozzolan

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Synonyms	Product Identifier	%	GHS US classification
Silica, amorphous	Amorphous silica / Silica / Silica, amorphous, fumed / Silica, colloidal / Silicon dioxide / Silicon dioxide, amorphous / Silicon(IV) oxide / Un-crystalline silica / Pigment White 27 / Silicon(IV)oxide / Silica amorphous / Silicon dioxide containing crystalline and amorphous / Fumed silica	(CAS-No.) 7631-86-9	1 – 75	Not classified
Quartz	Quartz (SiO ₂) / Silica, crystalline, quartz / Crystalline silica, quartz / .alpha.-Quartz / Silica, crystalline, .alpha.-quartz / Crystalline silica in the form of quartz / Quartz, silica / Quartz (respirable fraction) / Silica dust / Silica, crystalline-.alpha.quartz / Silica, .alpha.-quartz / Silicon dioxide / Silica, quartz / Silica, crystalline / Quartz (crystalline silica) / Silica dust, crystalline / Silica, crystalline (quartz)	(CAS-No.) 14808-60-7	1 – 50	Carc. 1A, H350 STOT SE 3, H335 STOT RE 1, H372
Aluminum oxide (Al ₂ O ₃)	Aluminum oxide / .alpha.-Alumina / Alumina / Aluminium oxide / .alpha.-Aluminum oxide / Alundum / Dialuminum trioxide	(CAS-No.) 1344-28-1	1 – 25	Not classified
Silica, cristobalite	Cristobalite / Cristobalite (SiO ₂) / Silica, crystalline, cristobalite / Cristobalite (Silica) / Crystalline SiO ₂ , cristobalite / Crystalline silica in the form of cristobalite / Silica / Silica, crystalline	(CAS-No.) 14464-46-1	≤ 5	Carc. 1A, H350 STOT RE 1, H372
Calcium oxide	Lime / Quicklime / Quicklime (CaO) / Calcium oxide (CaO) / Lime (calcium oxide)	(CAS-No.) 1305-78-8	≤ 5	Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 3, H402 Aquatic Chronic 3, H412
Sodium oxide (Na ₂ O)	Disodium oxide / Sodium oxide / Sodium monoxide	(CAS-No.) 1313-59-3	≤ 5	Skin Corr. 1B, H314 Eye Dam. 1, H318
Potassium oxide (K ₂ O)	Potassium oxide / Dipotassium oxide / Potassium monoxide	(CAS-No.) 12136-45-7	≤ 5	Skin Corr. 1A, H314 Eye Dam. 1, H318
Iron oxide (Fe ₂ O ₃)	C.I. 77491 / C.I. Pigment Red 101 / Diiron trioxide / Ferric oxide / Iron sesquioxide / Iron(III) oxide / Rouge / Iron trioxide / Sienna / Pigment Red 101 / Red iron oxide / Red iron oxide pigment / Diiron(III) trioxide / Iron oxide / Ferric oxide red / Iron oxide, red	(CAS-No.) 1309-37-1	≤ 5	Comb. Dust
Magnesium oxide (MgO)	Calcined magnesite / Magnesium oxide / Magnesia	(CAS-No.) 1309-48-4	< 1	Not classified
Titanium dioxide	C.I. 77891 / C.I. Pigment White 6 / Titanium oxide (TiO ₂) / Titanium(IV) oxide / C.I. Pigment White 7 / Pigment White 6 / Titanium dioxide nanoparticles / Titanium oxide	(CAS-No.) 13463-67-7	< 1	Carc. 2, H351

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Pozzolan

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid Measures After Inhalation: Using proper respiratory protection, move the exposed person to fresh air at once. Encourage exposed person to cough, spit out, and blow nose to remove dust. Immediately call a poison center, physician, or emergency medical service.

First-aid Measures After Skin Contact: Remove contaminated clothing. Immediately flush skin with plenty of water for at least 60 minutes. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or doctor.

First-aid Measures After Eye Contact: Rinse cautiously with water for at least 60 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid Measures After Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

Symptoms/Injuries: May cause respiratory irritation. Causes severe skin burns and eye damage. May cause cancer (Inhalation). Causes damage to organs (lung/respiratory system) through prolonged or repeated exposure (Inhalation).

Symptoms/Injuries After Inhalation: Irritation of the respiratory tract and the other mucous membranes. May be corrosive to the respiratory tract.

Symptoms/Injuries After Skin Contact: Causes severe irritation which will progress to chemical burns.

Symptoms/Injuries After Eye Contact: Causes permanent damage to the cornea, iris, or conjunctiva.

Symptoms/Injuries After Ingestion: May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

Chronic Symptoms: Long term exposure to respirable crystalline silica results in a significant risk of developing silicosis and other non-malignant respiratory disease, lung cancer, kidney effects, and immune system effects.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Water spray, dry chemical, foam, carbon dioxide.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable.

Explosion Hazard: Product is not explosive.

Reactivity: May react exothermically with water releasing heat. Adding an acid to a base or base to an acid may cause a violent reaction.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Metal oxides. Silicon oxides.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not breathe dust. Do not get in eyes, on skin, or on clothing. Do not handle until all safety precautions have been read and understood.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain solid spills with appropriate barriers and prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Recover the product by vacuuming, shoveling or sweeping. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Cautiously neutralize spilled solid.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

Pozzolan

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not get in eyes, on skin, or on clothing. Handle empty containers with care because they may still present a hazard. Do not breathe dust. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from Incompatible materials. Store in original container or corrosive resistant and/or lined container.

Incompatible Materials: Strong acids. Strong oxidizers.

7.3. Specific End Use(s)

No use is specified

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

Silica, amorphous (7631-86-9)		
USA NIOSH	NIOSH REL TWA	6 mg/m ³
USA IDLH	IDLH	3000 mg/m ³
USA OSHA	OSHA PEL TWA	6 mg/m ³
USA OSHA	OSHA PEL TWA	20 mppcf (80mg/m ³ /%SiO ₂)
Quartz (14808-60-7)		
USA ACGIH	ACGIH OEL TWA	0.025 mg/m ³ (respirable particulate matter)
USA ACGIH	ACGIH chemical category	A2 - Suspected Human Carcinogen
USA NIOSH	NIOSH REL TWA	0.05 mg/m ³ (respirable dust)
USA IDLH	IDLH	50 mg/m ³ (respirable dust)
USA OSHA	OSHA PEL TWA	50 µg/m ³ (Respirable crystalline silica)
USA OSHA	OSHA PEL TWA	(250)/(%SiO ₂ +5) mppcf TWA (respirable fraction) (10)/(%SiO ₂ +2) mg/m ³ TWA (respirable fraction) (For any operations or sectors for which the respirable crystalline silica standard, 1910.1053, is stayed or otherwise not in effect, See 20 CFR 1910.1000 TABLE Z-3)
Silica, cristobalite (14464-46-1)		
USA ACGIH	ACGIH OEL TWA	0.025 mg/m ³ (respirable particulate matter)
USA ACGIH	ACGIH chemical category	Suspected Human Carcinogen
USA NIOSH	NIOSH REL TWA	0.05 mg/m ³ (respirable dust)
USA IDLH	IDLH	25 mg/m ³ (respirable dust)
USA OSHA	OSHA PEL TWA	50 µg/m ³ (Respirable crystalline silica)
USA OSHA	OSHA PEL TWA	(1/2)(250)/(%SiO ₂ +5) mppcf (respirable fraction) (1/2)(10)/(%SiO ₂ +2) mg/m ³ (respirable fraction) (For any operations or sectors for which the respirable crystalline silica standard, 1910.1053, is stayed or otherwise not in effect, See 29 CFR 1910.1000 TABLE Z-3)
Aluminum oxide (Al ₂ O ₃) (1344-28-1)		
USA ACGIH	ACGIH OEL TWA	10 mg/m ³
USA OSHA	OSHA PEL TWA	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
Calcium oxide (1305-78-8)		
USA ACGIH	ACGIH OEL TWA	2 mg/m ³
USA NIOSH	NIOSH REL TWA	2 mg/m ³
USA IDLH	IDLH	25 mg/m ³
USA OSHA	OSHA PEL TWA	5 mg/m ³
Magnesium oxide (MgO) (1309-48-4)		
USA ACGIH	ACGIH OEL TWA	10 mg/m ³ (inhalable particulate matter)

Pozzolan

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA IDLH	IDLH	750 mg/m ³ (fume)
USA OSHA	OSHA PEL TWA	15 mg/m ³ (fume, total particulate)
Titanium dioxide (13463-67-7)		
USA ACGIH	ACGIH OEL TWA	10 mg/m ³
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA NIOSH	NIOSH REL TWA	2.4 mg/m ³ (CIB 63-fine) 0.3 mg/m ³ (CIB 63-ultrafine, including engineered nanoscale)
USA IDLH	IDLH	5000 mg/m ³
USA OSHA	OSHA PEL TWA	15 mg/m ³ (total dust)
Iron oxide (Fe₂O₃) (1309-37-1)		
USA ACGIH	ACGIH OEL TWA	5 mg/m ³ (respirable particulate matter)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA NIOSH	NIOSH REL TWA	5 mg/m ³ (dust and fume)
USA IDLH	IDLH	2500 mg/m ³ (dust and fume)
USA OSHA	OSHA PEL TWA	10 mg/m ³ (fume) 15 mg/m ³ (total dust (Rouge)) 5 mg/m ³ (respirable fraction (Rouge))


8.2. Exposure Controls

Appropriate Engineering Controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment

: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing

: Chemically resistant materials and fabrics. Corrosion-proof clothing.

Hand Protection

: Wear protective gloves.

Eye and Face Protection

: Chemical safety goggles.

Skin and Body Protection

: Wear suitable protective clothing.

Respiratory Protection

: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection. Respirators should be selected by and used under the direction of a trained health and safety professional, following requirements found in OSHA's respirator standard (29 CFR 1910.134).

Other Information

: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Solid
Appearance	: Light grey
Odor	: No data available
Odor Threshold	: No data available
pH	: 10 – 11.5
Evaporation Rate	: No data available
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: No data available
Flash Point	: No data available
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor Pressure	: No data available
Relative Vapor Density at 20°C	: No data available

Pozzolan

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative Density	: No data available
Solubility	: No data available
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: No data available

9.2. Other Information

No additional information available

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

May react exothermically with water releasing heat. Adding an acid to a base or base to an acid may cause a violent reaction.

10.2. Chemical Stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

10.4. Conditions to Avoid

Incompatible materials.

10.5. Incompatible Materials

Strong acids. Strong oxidizers.

10.6. Hazardous Decomposition Products

Crystalline silica (quartz) will dissolve in hydrofluoric acid and produce a corrosive gas – silicon tetrafluoride.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects

Acute Toxicity (Oral): Not classified

Acute Toxicity (Dermal): Not classified

Acute Toxicity (Inhalation): Not classified

Silica, amorphous (7631-86-9)	
LD50 Oral Rat	7900 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg (No deaths)
Quartz (14808-60-7)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rat	> 5000 mg/kg
Aluminum oxide (Al ₂ O ₃) (1344-28-1)	
LD50 Oral Rat	> 15900 mg/kg
Calcium oxide (1305-78-8)	
LD50 Oral Rat	> 2000 mg/kg
LD50 Dermal Rabbit	> 2500 mg/kg
LC50 Inhalation Rat	> 6.04 mg/l/4h
Magnesium oxide (MgO) (1309-48-4)	
LD50 Oral Rat	3870 mg/kg
Titanium dioxide (13463-67-7)	
LD50 Oral Rat	> 10000 mg/kg
LC50 Inhalation Rat	5.09 mg/l/4h
Iron oxide (Fe ₂ O ₃) (1309-37-1)	
LD50 Oral Rat	> 10000 mg/kg

Skin Corrosion/Irritation: Causes severe skin burns.

pH: 10 – 11.5

Serious Eye Damage/Irritation: Causes serious eye damage.

pH: 10 – 11.5

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Carcinogenicity: May cause cancer (Inhalation).

Silica, amorphous (7631-86-9)	
IARC group	3
Quartz (14808-60-7)	
IARC group	1

Pozzolan

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

National Toxicology Program (NTP) Status	Known Human Carcinogens.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
Silica, cristobalite (14464-46-1)	
IARC group	1
National Toxicology Program (NTP) Status	Known Human Carcinogens.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
Titanium dioxide (13463-67-7)	
IARC group	2B
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
Iron oxide (Fe₂O₃) (1309-37-1)	
IARC group	3

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): May cause respiratory irritation.

Specific Target Organ Toxicity (Repeated Exposure): Causes damage to organs (lung/respiratory system) through prolonged or repeated exposure (Inhalation).

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Irritation of the respiratory tract and the other mucous membranes. May be corrosive to the respiratory tract.

Symptoms/Injuries After Skin Contact: Causes severe irritation which will progress to chemical burns.

Symptoms/Injuries After Eye Contact: Causes permanent damage to the cornea, iris, or conjunctiva.

Symptoms/Injuries After Ingestion: May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

Chronic Symptoms: Long term exposure to respirable crystalline silica results in a significant risk of developing silicosis and other non-malignant respiratory disease, lung cancer, kidney effects, and immune system effects.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General : Not classified.

Silica, amorphous (7631-86-9)	
LC50 Fish	5000 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])
EC50 Crustacea	7600 mg/l (Exposure time: 48 h - Species: Ceriodaphnia dubia)
Aluminum oxide (Al₂O₃) (1344-28-1)	
LC50 Fish	> 100 mg/l
EC50 Crustacea	> 100 mg/l
ErC50 Algae	> 100 mg/l
NOEC (Acute)	> 50 mg/l
Calcium oxide (1305-78-8)	
LC50 Fish	50.6 mg/l
Iron oxide (Fe₂O₃) (1309-37-1)	
LC50 Fish	100000 mg/l (Exposure time: 96 h - Species: Danio rerio [static])

12.2. Persistence and Degradability

Pozzolan	
Persistence and Degradability	Not established.

12.3. Bioaccumulative Potential

Pozzolan	
Bioaccumulative Potential	Not established.
Silica, amorphous (7631-86-9)	
BCF Fish	No bioaccumulation expected.
Calcium oxide (1305-78-8)	
BCF Fish	No bioaccumulation.

12.4. Mobility in Soil

No additional information available

12.5. Other Adverse Effects

Other Information : Avoid release to the environment.

Pozzolan

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste Treatment Methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, and international regulations.

Additional Information: Container may remain hazardous when empty. Continue to observe all precautions.

Ecology - Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT

Proper Shipping Name : CORROSIVE SOLIDS, N.O.S. (CONTAINS POTASSIUM OXIDE, CALCIUM OXIDE)
Hazard Class : 8
Identification Number : UN1759
Label Codes : 8
Packing Group : II
ERG Number : 154



14.2. In Accordance with IMDG

Proper Shipping Name : CORROSIVE SOLID, N.O.S. (CONTAINS POTASSIUM OXIDE, CALCIUM OXIDE)
Hazard Class : 8
Identification Number : UN1759
Packing Group : II
Label Codes : 8
EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-B



14.3. In Accordance with IATA

Proper Shipping Name : CORROSIVE SOLID, N.O.S. (CONTAINS POTASSIUM OXIDE, CALCIUM OXIDE)
Packing Group : II
Identification Number : UN1759
Hazard Class : 8
Label Codes : 8
ERG Code (IATA) : 8L



SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

Pozzolan	
SARA Section 311/312 Hazard Classes	Health hazard - Carcinogenicity Health hazard - Serious eye damage or eye irritation Health hazard - Skin corrosion or Irritation Health hazard - Specific target organ toxicity (single or repeated exposure)
Silica, amorphous (7631-86-9)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Quartz (14808-60-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Silica, cristobalite (14464-46-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Aluminum oxide (Al₂O₃) (1344-28-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Calcium oxide (1305-78-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Magnesium oxide (MgO) (1309-48-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Sodium oxide (Na₂O) (1313-59-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Potassium oxide (K₂O) (12136-45-7)	

Pozzolan

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Titanium dioxide (13463-67-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Iron oxide (Fe₂O₃) (1309-37-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

SARA 313	Product name	CAS#	Wt%
Form R-Reporting Requirements	Aluminum oxide Lead (Organic or Inorganic)	1344-28-1 -	1-25 < 0.1

15.2. US State Regulations

Silica, amorphous (7631-86-9)

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

Quartz (14808-60-7)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

Silica, cristobalite (14464-46-1)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

Aluminum oxide (Al₂O₃) (1344-28-1)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

Calcium oxide (1305-78-8)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

Magnesium oxide (MgO) (1309-48-4)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

Potassium oxide (K₂O) (12136-45-7)

U.S. - New Jersey - Right to Know Hazardous Substance List

Titanium dioxide (13463-67-7)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

Iron oxide (Fe₂O₃) (1309-37-1)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

California Proposition 65



WARNING: This product can expose you to Quartz, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Chemical Name (CAS No.)	Carcinogenicity	Developmental Toxicity	Female Reproductive Toxicity	Male Reproductive Toxicity
Quartz (14808-60-7)	X			
Silica, cristobalite (14464-46-1)	X			
Titanium dioxide (13463-67-7)	X			

Pozzolan

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revision : 07/12/2022

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200

GHS Full Text Phrases:

H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H335	May cause respiratory irritation
H350	May cause cancer
H351	Suspected of causing cancer
H372	Causes damage to organs through prolonged or repeated exposure
H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

SDS US (GHS HazCom)