

## SECTION 1: IDENTIFICATION

### 1.1. Product Identifier

**Product Form:** Mixture

**Product Name:** Cold Mix Asphalt, Cutback Asphalt

### 1.2. Intended Use of the Product

**Use of the Substance/Mixture:** No use is specified

### 1.3. Name, Address, and Telephone of the Responsible Party

**Company**

CalPortland Company  
 10655 W Park Run Drive, Suite 275  
 Las Vegas, NV 89144  
 T 626-852-6200

[www.calportland.com](http://www.calportland.com)

### 1.4. Emergency Telephone Number

**Emergency Number** : 626-852-6200

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the Substance or Mixture

|           |      |
|-----------|------|
| Carc. 1A  | H350 |
| STOT SE 3 | H335 |
| STOT RE 1 | H372 |

Full text of hazard classes and H-statements : see section 16

### 2.2. Label Elements

#### GHS-US Labeling

**Hazard Pictograms (GHS-US)** :



**Signal Word (GHS-US)** :

Danger

**Hazard Statements (GHS-US)** :

H335 - May cause respiratory irritation.  
 H350 - May cause cancer (Inhalation).  
 H372 - Causes damage to organs (lung/respiratory system) through prolonged or repeated exposure (Inhalation).

**Precautionary Statements (GHS-US)** :

P201 - Obtain special instructions before use.  
 P202 - Do not handle until all safety precautions have been read and understood.  
 P260 - Do not breathe vapors, mist, spray, dust, fume.  
 P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.  
 P270 - Do not eat, drink or smoke when using this product.  
 P271 - Use only outdoors or in a well-ventilated area.  
 P280 - Wear protective gloves, protective clothing, and eye protection.  
 P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.  
 P308+P313 - If exposed or concerned: Get medical advice/attention.  
 P312 - Get medical advice/attention if you feel unwell.  
 P314 - Get medical advice/attention if you feel unwell.  
 P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
 P405 - Store locked up.  
 P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

### 2.3. Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. At elevated temperatures, this product will cause thermal burns and may release toxic hydrogen sulfide (H2S). Hydrogen sulfide is a fatal and highly flammable gas with a rotten egg odor that quickly causes odor fatigue. Explosion can occur if hydrogen sulfide is allowed to accumulate in the headspace of closed systems in the presence of an ignition source.

# Cold Mix Asphalt, Cutback Asphalt

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## 2.4. Unknown Acute Toxicity (GHS-US)

No data available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substance

Not applicable

### 3.2. Mixture

| Name                                       | Product Identifier     | %       | GHS-US classification                                |
|--|------------------------|---------|--|
| Aggregate (crushed stone, sand and gravel) | (CAS-No.) Not assigned | 90 - 95 | Not classified                                       |
| Quartz                                     | (CAS-No.) 14808-60-7   | 10 - 90 | Carc. 1A, H350<br>STOT SE 3, H335<br>STOT RE 1, H372 |
| Asphalt                                    | (CAS-No.) 8052-42-4    | 5 - 10  | Carc. 2, H351  |

Full text of H-phrases: see section 16

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of First-aid Measures

**First-aid Measures General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**First-aid Measures After Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

**First-aid Measures After Skin Contact:** Rinse immediately with plenty of water. Obtain medical attention if irritation develops or persists. In molten form: Cool skin rapidly with cold water after contact with molten product. Removal of solidified molten material from skin requires medical assistance. Seek medical attention for thermal burns.

**First-aid Measures After Eye Contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. In molten form: Flush with large amounts of water, lifting upper and lower lids occasionally. Remove contact lenses, if present and easy to do. Get medical attention. Obtain medical attention for thermal burns.

**First-aid Measures After Ingestion:** Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

### 4.2. Most Important Symptoms and Effects Both Acute and Delayed

**Symptoms/Injuries:** May cause respiratory irritation. May cause cancer. Causes damage to organs through prolonged or repeated exposure. This product, if heated may release asphalt fumes. During processing, inhalation of fumes may cause dizziness and/or irritation to the eyes, nose, and throat. Hot molten product will cause thermal burns to the skin.

**Symptoms/Injuries After Inhalation:** Toxic fumes may be generated from heating asphalt and may be harmful if inhaled. Prolonged exposure may cause irritation. WARNING: irritating and toxic hydrogen sulfide gas may be present. Greater than 15-20ppm continuous exposure can cause mucous membrane and respiratory tract irritation. 50-500 ppm can cause headache, nausea, and dizziness. Continued exposure at these levels can lead to loss of reasoning and balance, difficulty in breathing, fluid in the lungs, and possible loss of consciousness. Greater than 500ppm can cause rapid unconsciousness and death if not promptly revived. For particulates and dust: Cough, dyspnea (breathing difficulty), wheezing; decreased pulmonary function, progressive respiratory symptoms (silicosis). Accelerated Silicosis can occur with exposure to high concentrations of respirable crystalline silica over a relatively short period; lung lesions can appear within five years of the initial exposure. The progression can be rapid. Accelerated silicosis is similar to chronic or ordinary silicosis, except that lung lesions appear earlier and the progression is more rapid. Acute Silicosis can occur with exposures to very high concentrations of respirable crystalline silica over a very short time period, sometimes as short as a few months. The symptoms of acute silicosis include progressive shortness of breath, fever, cough and weight loss. Acute silicosis can be fatal.

**Symptoms/Injuries After Skin Contact:** Prolonged exposure may cause skin irritation. Risk of thermal burns on contact with molten product.

**Symptoms/Injuries After Eye Contact:** Eye contact with dust may cause mechanical irritation. Risk of thermal burns on contact with molten product.

**Symptoms/Injuries After Ingestion:** Ingestion may cause adverse effects. Ingestion may cause nausea, vomiting and diarrhea.

**Chronic Symptoms:** According to the International Agency for Research on Cancer (IARC), exposure to asphalt fumes is probably carcinogenic to humans. For particulates and dust: Pre-existing lung diseases such as emphysema or asthma may be aggravated by exposure to dusts. Pulmonary function may be reduced by inhalation of respirable crystalline silica. Also lung scarring produced by such inhalation may lead to a progressive massive fibrosis of the lung which may aggravate other pulmonary conditions and diseases and which increases susceptibility to pulmonary tuberculosis. Progressive massive fibrosis may be accompanied by right heart enlargement, heart failure, and pulmonary failure. Smoking aggravates the effects of exposure.

# Cold Mix Asphalt, Cutback Asphalt

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

## SECTION 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Water spray, fog, carbon dioxide (CO<sub>2</sub>), alcohol-resistant foam, or dry chemical.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire. Do not use water when molten material is involved, contact of hot product with water will result in a violent expansion as the water turns to steam causing explosion with massive force.

### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Not considered flammable but may burn at high temperatures.

**Explosion Hazard:** Product may release explosive hydrogen sulfide gas.

**Reactivity:** Hazardous reactions will not occur under normal conditions.

### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Do not get in eyes or on skin. Do not breathe dust or fumes.

#### 6.1.1. For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protective equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### 6.1.2. For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Ventilate area. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

### 6.2. Environmental Precautions

Prevent entry to sewers and public waters.

### 6.3. Methods and Materials for Containment and Cleaning Up

**For Containment:** Where possible allow molten material to solidify naturally. Contain solid spills with appropriate barriers and prevent migration and entry into sewers or streams.

**Methods for Cleaning Up:** Allow liquid material to solidify before cleaning up. Clean up spills immediately and dispose of waste safely. Recover the product by vacuuming, shoveling or sweeping. Avoid generation of dust during clean-up of spills. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

### 6.4. Reference to Other Sections

See Heading 8. Exposure controls and personal protection. See Section 13, Disposal Considerations.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

**Additional Hazards When Processed:** May release poisonous hydrogen sulfide. Hydrogen sulfide is a highly flammable, explosive gas under certain conditions, is a toxic gas, and may be fatal. Gas can accumulate in the headspace of closed containers, use caution when opening sealed containers. Heating the product or containers can cause thermal decomposition of the product and release hydrogen sulfide.

**Precautions for Safe Handling:** Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid prolonged contact with eyes and skin. Do not handle until all safety precautions have been read and understood. Do not breathe dust or fumes.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Deposits (carbonaceous materials and iron sulphides) can develop on the internal walls and roofs of tanks in case of long term storage. These deposits may be pyrophoric and self-ignite in contact with the air. Comply with applicable regulations.

**Storage Conditions:** Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

**Incompatible Materials:** Strong oxidizers.

# Cold Mix Asphalt, Cutback Asphalt

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## 7.3. Specific End Use(s)

No use is specified

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

| Asphalt (8052-42-4) |  |   |
|---------------------|--|---|
| USA ACGIH           | ACGIH TWA (mg/m <sup>3</sup> )           | 0.5 mg/m <sup>3</sup> (fume, inhalable particulate matter)  |
| USA ACGIH           | ACGIH chemical category                  | Not Classifiable as a Human Carcinogen fume, coal tar-free  |
| USA ACGIH           | Biological Exposure Indices (BEI)        | Parameter: 1-Hydroxypyrene with hydrolysis - Medium: urine - Sampling time: end of shift at end of workweek (nonquantitative) |
| USA NIOSH           | NIOSH REL (ceiling) (mg/m <sup>3</sup> ) | 5 mg/m <sup>3</sup> (fume)  |
| Quartz (14808-60-7) |  |   |
| USA ACGIH           | ACGIH TWA (mg/m <sup>3</sup> )           | 0.025 mg/m <sup>3</sup> (respirable particulate matter)   |
| USA ACGIH           | ACGIH chemical category                  | A2 - Suspected Human Carcinogen   |
| USA NIOSH           | NIOSH REL (TWA) (mg/m <sup>3</sup> )     | 0.05 mg/m <sup>3</sup> (respirable dust)  |
| USA IDLH            | US IDLH (mg/m <sup>3</sup> )             | 50 mg/m <sup>3</sup> (respirable dust)  |
| USA OSHA            | OSHA PEL (TWA) (mg/m <sup>3</sup> )      | 50 µg/m <sup>3</sup>  |


### 8.2. Exposure Controls

#### Appropriate Engineering Controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Gas detectors should be used when toxic gases may be released. Gas detectors should be used when flammable gases or vapors may be released

#### Personal Protective Equipment

: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



#### Materials for Protective Clothing

: Chemically resistant materials and fabrics.

#### Hand Protection

: Wear protective gloves.

#### Eye and Face Protection

: Chemical safety goggles.

#### Skin and Body Protection

: Wear suitable protective clothing.

#### Respiratory Protection

: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

#### Thermal Hazard Protection

: When working with hot material, use suitable thermally protective clothing.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

|                           |                        |
|---------------------------|------------------------|
| Physical State            | : Solid                |
| Appearance                | : Coarse, black        |
| Odor                      | : Petroleum            |
| Odor Threshold            | : No data available    |
| pH                        | : No data available    |
| Evaporation Rate          | : No data available    |
| Melting Point             | : No data available    |
| Freezing Point            | : No data available    |
| Boiling Point             | : > 350 °C (662 °F)    |
| Flash Point               | : > 260 °F (126.67 °C) |
| Auto-ignition Temperature | : No data available    |
| Decomposition Temperature | : No data available    |
| Flammability (solid, gas) | : No data available    |

# Cold Mix Asphalt, Cutback Asphalt

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|  |                     |
|--|---------------------|
| Vapor Pressure                         | : No data available |
| Relative Vapor Density at 20°C         | : No data available |
| Relative Density                       | : No data available |
| Specific Gravity                       | : 2.2 - 2.5         |
| Solubility                             | : No data available |
| Partition Coefficient: N-Octanol/Water | : No data available |
| Viscosity                              | : No data available |

9.2. **Other Information** No additional information available

## SECTION 10: STABILITY AND REACTIVITY

- 10.1. **Reactivity:** Hazardous reactions will not occur under normal conditions.
- 10.2. **Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3. **Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. **Conditions to Avoid:** Incompatible materials.
- 10.5. **Incompatible Materials:** Strong oxidizers.
- 10.6. **Hazardous Decomposition Products:** Thermal decomposition generates: Hydrogen sulfide. Carbon oxides (CO, CO<sub>2</sub>). Sulfur oxides. Nitrogen oxides. Organic compounds.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on Toxicological Effects

**Acute Toxicity:** Not classified

|                            |                          |
|----------------------------|--------------------------|
| <b>Asphalt (8052-42-4)</b> |                          |
| LD50 Oral Rat              | > 5000 mg/kg             |
| LD50 Dermal Rabbit         | > 2000 mg/kg             |
| LC50 Inhalation Rat        | > 94.4 mg/m <sup>3</sup> |
| <b>Quartz (14808-60-7)</b> |                          |
| LD50 Oral Rat              | > 5000 mg/kg             |
| LD50 Dermal Rat            | > 5000 mg/kg             |

**Skin Corrosion/Irritation:** Not classified

**Serious Eye Damage/Irritation:** Not classified

**Respiratory or Skin Sensitization:** Not classified

**Germ Cell Mutagenicity:** Not classified

**Carcinogenicity:** May cause cancer (Inhalation).

|   |   |
|---|---|
| <b>Asphalt (8052-42-4)</b>                |   |
| IARC group                                | 2B  |
| OSHA Hazard Communication Carcinogen List | In OSHA Hazard Communication Carcinogen list. |
| <b>Quartz (14808-60-7)</b>                |   |
| IARC group                                | 1   |
| National Toxicology Program (NTP) Status  | Known Human Carcinogens.                      |
| OSHA Hazard Communication Carcinogen List | In OSHA Hazard Communication Carcinogen list. |

**Reproductive Toxicity:** Not classified

**Specific Target Organ Toxicity (Single Exposure):** May cause respiratory irritation.

**Specific Target Organ Toxicity (Repeated Exposure):** Causes damage to organs (lung/respiratory system) through prolonged or repeated exposure (Inhalation).

**Aspiration Hazard:** Not classified

# Cold Mix Asphalt, Cutback Asphalt

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Symptoms/Injuries After Inhalation:** Toxic fumes may be generated from heating asphalt and may be harmful if inhaled. Prolonged exposure may cause irritation. **WARNING:** irritating and toxic hydrogen sulfide gas may be present. Greater than 15-20ppm continuous exposure can cause mucous membrane and respiratory tract irritation. 50-500 ppm can cause headache, nausea, and dizziness. Continued exposure at these levels can lead to loss of reasoning and balance, difficulty in breathing, fluid in the lungs, and possible loss of consciousness. Greater than 500ppm can cause rapid unconsciousness and death if not promptly revived. For particulates and dust: Cough, dyspnea (breathing difficulty), wheezing; decreased pulmonary function, progressive respiratory symptoms (silicosis). Accelerated Silicosis can occur with exposure to high concentrations of respirable crystalline silica over a relatively short period; lung lesions can appear within five years of the initial exposure. The progression can be rapid. Accelerated silicosis is similar to chronic or ordinary silicosis, except that lung lesions appear earlier and the progression is more rapid. Acute Silicosis can occur with exposures to very high concentrations of respirable crystalline silica over a very short time period, sometimes as short as a few months. The symptoms of acute silicosis include progressive shortness of breath, fever, cough and weight loss. Acute silicosis can be fatal.

**Symptoms/Injuries After Skin Contact:** Prolonged exposure may cause skin irritation. Risk of thermal burns on contact with molten product.

**Symptoms/Injuries After Eye Contact:** Eye contact with dust may cause mechanical irritation. Risk of thermal burns on contact with molten product.

**Symptoms/Injuries After Ingestion:** Ingestion may cause adverse effects. Ingestion may cause nausea, vomiting and diarrhea.

**Chronic Symptoms:** According to the International Agency for Research on Cancer (IARC), exposure to asphalt fumes is probably carcinogenic to humans. For particulates and dust: Pre-existing lung diseases such as emphysema or asthma may be aggravated by exposure to dusts. Pulmonary function may be reduced by inhalation of respirable crystalline silica. Also lung scarring produced by such inhalation may lead to a progressive massive fibrosis of the lung which may aggravate other pulmonary conditions and diseases and which increases susceptibility to pulmonary tuberculosis. Progressive massive fibrosis may be accompanied by right heart enlargement, heart failure, and pulmonary failure. Smoking aggravates the effects of exposure.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

Ecology - General : Not classified.

### 12.2. Persistence and Degradability

|                                   |                  |
|-----------------------------------|------------------|
| Cold Mix Asphalt, Cutback Asphalt |                  |
| Persistence and Degradability     | Not established. |

### 12.3. Bioaccumulative Potential

|                                   |                               |
|-----------------------------------|-------------------------------|
| Cold Mix Asphalt, Cutback Asphalt |                               |
| Bioaccumulative Potential         | Not established.              |
| Asphalt (8052-42-4)               |                               |
| BCF Fish 1                        | (no bioaccumulation expected) |
| Log Pow                           | > 6                           |

12.4. Mobility in Soil No additional information available

### 12.5. Other Adverse Effects

Other Information : Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste Treatment Methods

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, and international regulations.

**Additional Information:** Container may remain hazardous when empty. Continue to observe all precautions.

**Ecology - Waste Materials:** Avoid release to the environment.

## SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

### 14.1. In Accordance with DOT

Proper Shipping Name : ELEVATED TEMPERATURE LIQUID, N.O.S. (asphalt)  
Hazard Class : 9  
Identification Number : UN3257  
Label Codes : 9  
Packing Group : III  
ERG Number : 128



# Cold Mix Asphalt, Cutback Asphalt

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## 14.2. In Accordance with IMDG

**Proper Shipping Name** : ELEVATED TEMPERATURE LIQUID, N.O.S. (asphalt)  
**Hazard Class** : 9  
**Identification Number** : UN3257  
**Packing Group** : III  
**Label Codes** : 9  
**EmS-No. (Fire)** : F-A  
**EmS-No. (Spillage)** : S-P



## 14.3. In Accordance with IATA

**Proper Shipping Name** : ELEVATED TEMPERATURE LIQUID, N.O.S. (asphalt)  
**Identification Number** : UN3257  
**Hazard Class** : 9  
**Label Codes** : 9  
**ERG Code (IATA)** : 9L



## SECTION 15: REGULATORY INFORMATION

### 15.1. US Federal Regulations

|   |  |
|---|--|
| <b>Cold Mix Asphalt, Cutback Asphalt</b>                                  |  |
| <b>SARA Section 311/312 Hazard Classes</b>                                | Immediate (acute) health hazard<br>Delayed (chronic) health hazard |
| <b>Asphalt (8052-42-4)</b>  |  |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |  |
| <b>Quartz (14808-60-7)</b>  |  |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |  |

### 15.2. US State Regulations



**WARNING:** This product can expose you to chemicals including Silica, crystalline (airborne particles of respirable size), a chemical known to the State of California to cause cancer; and Lead and Lead Compounds, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

|   |
|---|
| <b>Asphalt (8052-42-4)</b>  |
| U.S. - Massachusetts - Right To Know List<br>U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) List |
| <b>Quartz (14808-60-7)</b>  |
| U.S. - Massachusetts - Right To Know List<br>U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) List |

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Date of Preparation or Latest Revision** : 07/31/2018  
**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200

### GHS Full Text Phrases:

|           |  |
|-----------|--|
| Carc. 1A  | Carcinogenicity Category 1A                                    |
| Carc. 2   | Carcinogenicity Category 2                                     |
| STOT RE 1 | Specific target organ toxicity (repeated exposure) Category 1  |
| STOT SE 3 | Specific target organ toxicity (single exposure) Category 3    |
| H335      | May cause respiratory irritation                               |
| H350      | May cause cancer   |
| H351      | Suspected of causing cancer                                    |
| H372      | Causes damage to organs through prolonged or repeated exposure |

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

# Cold Mix Asphalt, Cutback Asphalt

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

SDS US (GHS HazCom)